

MATERIAL SAFETY DATA SHEET



ND INDUSTRIES, INC.
1893 BARRETT ROAD
TROY, MICHIGAN 48084
(248) 288-0000 Fax: (248) 288-0022
24 hr. EMERGENCY CHEMTREC:
1-800-424-9300

PRODUCT: 310005 Instant Superglue

MSDS ID: ND2185

DATE: 11/13/98 Updated: 11/1/00

PREPARED BY: Chemical Safety

SECTION I -Material Identification and Information

H: 2

F: 2

R: 2

PPE: H

COMPONENTS

COMPONENTS	CAS #	PERCENT %	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Ethyl cyanoacrylate	7085-85-0	95-100	n.e.	n.e.	
Hydroquinone	123-31-9	0-0.5	n.e.	n.e.	

All ingredients are listed on the TSCA Inventory.

n.a.= not applicable / n.e.=not established

SECTION II -Physical and Chemical Characteristics

BOILING POINT:	> 300°F
VAPOR DENSITY:	approx. 3.0 air = 1
VAPOR PRESSURE:	<0.2 mmHg @ 75°F
MELTING POINT:	n.a.
SPECIFIC GRAVITY:	1.06 water = 1
EVAPORATION RATE:	n.a.
WATER REACTIVE:	Yes, polymerization
SOLUBILITY IN WATER:	No, polymerized by water
APPEARANCE AND ODOR:	Clear viscous liquid with sharp irritating odor

SECTION III - Fire and Explosion Hazard Data

FLASH POINT: 185°F	T.C.C.
AUTOIGNITION TEMPERATURE:	not determined
FLAMMABILITY LIMITS % IN AIR: LEL: n.a.	UEL: n.a.
EXTINGUISHER MEDIA:	Carbon dioxide, dry chemical or foam

SPECIAL FIREFIGHTING PROCEDURES: Wear a NIOSH approved self-contained breathing apparatus operated in pressure-demand or positive pressure when fighting fires.

UNUSUAL FIRE HAZARDS AND CONDITIONS TO AVOID: Possible exothermic reaction leading to substrate ignition and fume generation.

MATERIAL SAFETY DATA SHEET

PRODUCT: 310005 Instant Superglue

SECTION IV - Reactivity Hazard Data

STABILITY: **stable:** X **unstable:**
HAZARDOUS POLYMERIZATION: **may occur:** X **will not occur:**

CONDITIONS TO AVOID: Amines and basic materials.

INCOMPATIBILITY: Polymerized by contact with water, alcohols, amines, and alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: None

SECTION V - Health Hazard Data

PRIMARY ROUTES OF ENTRY: **INHALATION:** X **INGESTION:** X **SKIN ABSORPTION:** X

EYE CONTACT: Can cause irritation of the eyes. Can bond eyelids together. Wash thoroughly with warm water and apply gauze patch. Get medical attention. The eye will open without further action, typically in 1 to 4 days. **DO NOT try to open the eyes by physical manipulation.** Adhesion to eye proteins will disassociate over several hours. This will cause periods of weeping. Seek medical attention.

FIRST AID:

SKIN CONTACT: Can cause irritation, bonding and drying of the skin.

FIRST AID: Immerse bonded surface in warm soapy water. Peel or roll surface apart with the aid of a blunt instrument. Remove the adhesive from skin with warm, soapy water. DO NOT try to pull bonded surface apart as you may rip or tear your skin. Seek medical attention

INHALATION: Vapor may be mildly irritating.

FIRST AID: This vapor is relatively harmless. Remove victim to fresh air. Seek medical attention

INGESTION: Relatively unlikely since material will solidify and adhere to the mouth.

FIRST AID: Saliva will lift the material in approximately one half to 2 days. In case a lump forms in the mouth, position the patient to prevent ingestion of the lump when it detaches thus preventing choking. Seek medical attention.

CHRONIC EFFECTS: Not determined

Carcinogenic: Not listed.

MATERIAL SAFETY DATA SHEET

PRODUCT: 310005 Instant Superglue

Component	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl cyanoacrylate	not determined	not determined	not determined
Hydroquinone	not determined	not determined	not determined

SECTION VI - Control and Protective Measures

RESPIRATORY PROTECTION: Vapors are highly irritating to throat a respirator that protects against organic vapors should be worn at all times when handling, also work only in well ventilated areas.

PROTECTIVE GLOVES: Polyethylene gloves, DO NOT use cotton.

EYE PROTECTION: Vapors are highly irritating to eyes vapor proof goggles should be worn.

VENTILATION TO BE USED: LOCAL EXHAUST: MECHANICAL: SPECIFIC:
OTHER (specify): Positive down -draft exhaust ventilation should be provided to maintain vapor concentration below TLV

PROTECTIVE CLOTHING AND EQUIPMENT: Polyethylene apron.

HYGIENIC WORK PRACTICES: Always wash after using material.

SECTION VII - Precautions for Safe Handling and Spill/Leak Procedures

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED:

Flood with water to polymerize material. Soak up with absorbent material.

WASTE DISPOSAL METHODS: Collect polymerized material and dispose of according to local, state and federal regulations.

SAFE HANDLING AND STORAGE: Store at or below 75°F to maximize shelf life.

OTHER PRECAUTIONS AND SPECIAL HAZARDOUS INFORMATION:

Avoid contact with skin and eyes. Avoid breathing vapors.

**RECOMMENDED
NFPA/HMIS
RATING**

HEALTH 2

FLAMMABILITY 2

REACTIVITY 2

**PERSONAL H
PROTECTION**

note: ratings may differ according to application, environment, and physical state.

MATERIAL SAFETY DATA SHEET

PRODUCT: 310005 Instant Superglue

NOTES:

SECTION 313 SUPPLIER NOTIFICATION

Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included.

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CAS #</u>	<u>CHEMICAL NAME</u>	<u>% BY WEIGHT</u>
123-31-9	Hydroquinone	0-0.5

This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity.

<u>material</u>	<u>CAS #</u>	<u>Concentration</u> <u>%</u>	<u>cancer</u> <u>agent</u>	<u>Reproductive</u> <u>Toxin</u>	<u>cancer</u> <u>agent</u> & <u>Reproductive</u> <u>Toxin</u>
-----------------	--------------	----------------------------------	-------------------------------	-------------------------------------	---

The information contained herein is based on the data available to us and is believed to be correct. However, ND Industries®, Inc. makes no warranty, expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their properties prior to use. Since conditions of use are beyond our control, all risks are assumed by the user.