

# PRODUCT SUBMITTAL / SUBSTITUTION REQUEST

TO:

PROJECT:

SPECIFIED ITEM:

Section

Page

Paragraph

Description

## PRODUCT SUBMITTAL / SUBSTITUTION REQUESTED:

The attached submittal package includes the product description, specifications, drawings, and performance data for use in the evaluation of the request.

## SUBMITTED BY:

Name:

Signature:

Company:

Address:

Date:

Telephone:

Fax:

## FOR USE BY THE ARCHITECT AND/OR ENGINEER

**Approved**       **Approved as Noted**       **Not Approved**

(If not approved, please briefly explain why the product was not accepted.)

By:

Date:

Remarks:

**Mini Dropin™ Internally Threaded Expansion Anchor**

**PRODUCT DESCRIPTION**

The Mini Dropin is a carbon steel machine bolt anchor for use in shallow embedment applications. In addition to solid concrete and precast hollow core plank, it can be used in post-tensioned concrete slabs and concrete pours over steel deck.

**GENERAL APPLICATIONS AND USES**

- Suspending Conduit
- Cable Trays and Strut
- Pipe Supports
- Fire Sprinkler
- Utilities
- Suspended Lighting

**FEATURES AND BENEFITS**

- Anchor design allows for shallow embedment
- Internally threaded anchor for easy removability and service work
- Ideal for precast hollow core plank and post-tension concrete slabs
- Lip provides flush installation and consistent embedment
- Setting tool scores flange when set to verify proper expansion depth

**APPROVALS AND LISTINGS**

Tested in accordance with ASTM E 488 and AC01 criteria  
 Factory Mutual Research Corporation (FM Approvals) – File No. J.I. 3002071  
 See listing for applicable sizes - [www.fmglobal.com](http://www.fmglobal.com)

**GUIDE SPECIFICATIONS**

**CSI Divisions: 03151-Concrete Anchoring and 05090-Metal Fastenings.** Anchors shall be Mini Dropin anchors as supplied by Powers Fasteners, Inc., Brewster, NY.

**MATERIAL AND INSTALLATION SPECIFICATIONS**

**Material Specification**

Anchor Component	Carbon Steel
Anchor Body	SAE 1009
Plug	SAE 1009
Zinc Plating	ASTM B633, SC1, Type III (Fe/Zn 5)


**Installation Specification**

Dimension	Rod/Anchor Diameter, <i>d</i>		
	1/4"	3/8"	1/2"
ANSI Drill Bit Size, <i>d<sub>bit</sub></i> (in.)	3/8	1/2	5/8
Maximum Tightening Torque, <i>T<sub>max</sub></i> , (ft-lbs)	3	5	10
Thread Size (UNC)	1/4 - 20	3/8 - 16	1/2 - 13
Thread Depth (in.)	3/8	13/32	5/8
Overall Anchor Length (in.)	5/8	3/4	1


**Installation Guidelines**

Drill a hole into the base material to the depth of embedment required. The tolerances of the drill bit used must meet the requirements of ANSI Standard B212.15.


In post-tensioned concrete slabs, take care to avoid drilling into the post-tensioned cables.



Blow the hole clean of dust and other materials. Insert the anchor into the hole and tap flush with surface. Using a Powers setting tool specifically, set the anchor by driving the tool with a sufficient number of hammer blows until the shoulder of the tool is seated against the anchor. Anchor will not hold allowable loads required if shoulder of Powers setting tool does not seat against anchor.



If using a fixture, position it, insert bolt and tighten. Most overhead applications utilize threaded rod. Minimum thread engagement should be at least one anchor diameter.



**SECTION CONTENTS** Page No.

General Information..... 1

Material and Installation Specifications..... 1

Performance Data..... 3

Design Criteria..... 4

Ordering Information..... 4



Mini Dropin

**THREAD VERSION**

UNC Thread

**ANCHOR MATERIALS**

Zinc Plated Carbon Steel

**ROD/ANCHOR SIZE RANGE (TYP.)**

1/4" diameter to 1/2" diameter

**SUITABLE BASE MATERIALS**

- Normal-weight Concrete
- Structural Lightweight Concrete
- Precast Hollow Core Plank
- Concrete Over Steel Deck

**PERFORMANCE DATA**



**MECHANICAL ANCHORS**

**Ultimate Load Capacities for Mini Dropin in Normal-Weight Concrete<sup>1</sup>**

Rod/Anchor Size  <i>d</i> in. (mm)	Minimum Embedment Depth  <i>h<sub>v</sub></i> in. (mm)	Minimum Concrete Compressive Strength ( <i>f'<sub>c</sub></i> )					
		3,000 psi (20.7 MPa)		4,000 psi (27.6 MPa)		6,000 psi (41.4 MPa)	
		Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4 (6.4)	5/8 (15.9)	1,400 (6.3)	1,260 (5.7)	1,400 (6.3)	1,650 (7.4)	1,400 (6.3)	1,650 (7.4)
3/8 (9.5)	3/4 (19.1)	1,980 (8.9)	2,700 (12.2)	2,120 (9.5)	4,220 (19.0)	2,270 (10.2)	4,220 (19.0)
1/2 (12.7)	1 (25.4)	3,360 (15.1)	4,400 (19.8)	3,360 (15.1)	4,875 (21.9)	3,750 (16.9)	4,875 (21.9)

1. The values listed above are ultimate load capacities which should be reduced by a minimum safety factor of 4.0 or greater to determine the allowable working load. Consideration of safety factors of 10 or higher maybe necessary depending on the application such as life safety.


**Allowable Load Capacities for Mini Dropin in Normal-Weight Concrete<sup>1,2</sup>**

Rod/Anchor Size  <i>d</i> in. (mm)	Minimum Embedment Depth  <i>h<sub>v</sub></i> in. (mm)	Minimum Concrete Compressive Strength ( <i>f'<sub>c</sub></i> )					
		3,000 psi (20.7 MPa)		4,000 psi (27.6 MPa)		6,000 psi (41.4 MPa)	
		Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4 (6.4)	5/8 (15.9)	350 (1.6)	315 (1.4)	350 (1.6)	415 (1.9)	350 (1.6)	415 (1.9)
3/8 (9.5)	3/4 (19.1)	495 (2.2)	675 (3.0)	530 (2.4)	1,055 (4.7)	570 (2.6)	1,055 (4.7)
1/2 (12.7)	1 (25.4)	840 (3.8)	1,100 (5.0)	840 (3.8)	1,220 (5.5)	940 (4.2)	1,220 (5.5)

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0. Consideration of safety factors of 10 or higher maybe necessary depending on the application such as life safety.  
2. Linear interpolation may be used to determine allowable loads for intermediate compressive strengths.

**Ultimate and Allowable Load Capacities for Mini Dropin Installed Through Steel Deck into Structural Lightweight Concrete<sup>1,2,3</sup>**

Installation Detail for Mini Dropin Installed Through Soffit of Steel Deck into Concrete



Rod/Anchor Size  <i>d</i> in. (mm)	Minimum Embedment Depth  <i>h<sub>v</sub></i> in. (mm)	Lightweight Concrete Over Min. 20 Ga. Steel Deck. <i>f'<sub>c</sub></i> ≥ 3,000 psi (20.7 MPa)			
		Minimum 1-3/4" Wide Deck			
		Ultimate Load		Allowable Load	
		Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4 (6.4)	5/8 (15.9)	740 (3.3)	1,880 (8.5)	185 (0.8)	470 (2.1)
3/8 (9.5)	3/4 (19.1)	880 (4.0)	2,040 (9.2)	220 (1.0)	510 (2.3)
1/2 (12.7)	1 (25.4)	1,380 (6.2)	2,120 (9.5)	345 (1.6)	530 (2.4)

1. The metal deck shall be No. 22 gage to No. 18 gage thick steel [0.030-inch to 0.047-inch base metal thickness (0.75 mm to 1.20 mm)].  
2. Allowable load capacities are calculated using a safety factor of 4.0. Consideration of safety factors of 10 or higher maybe necessary depending on the application such as life safety.  
3. Tabulated load values are for anchors installed with a minimum edge distance of 7/8" when installed through the lower flute. Anchors installed through the upper flute may be in any location provided the proper installation procedures are maintained.




**PERFORMANCE DATA**

**Ultimate and Allowable Load Capacities for Mini Dropin in Precast Hollow Core Concrete Plank<sup>1</sup>**

Rod/ Anchor Size <i>d</i> in. (mm)	Minimum Embed. Depth <i>h<sub>v</sub></i> in. (mm)	Minimum Spacing in. (mm)	Minimum Edge Distance in. (mm)	Min. Concrete Compressive Strength <i>f'<sub>c</sub></i> ≥ 5,000 psi (34.5 MPa)			
				Ultimate Load		Allowable Load	
				Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4 (6.4)	5/8 (15.9)	3 (76.2)	3 (76.2)	2,360 (10.6)	1,840 (8.3)	590 (2.7)	460 (2.1)
3/8 (9.5)	3/4 (19.1)	4 1/2 (114.3)	4 1/2 (114.3)	2,600 (11.7)	3,400 (15.3)	650 (2.9)	850 (3.8)
1/2 (12.7)	1 (25.4)	6 (152.4)	6 (152.4)	2,600 (11.7)	3,540 (15.9)	650 (2.9)	885 (4.0)

Installation Detail for Mini Dropin Installed in Precast Hollow Core Concrete plank



1. Allowable loads are calculated using an applied safety factor of 4.0. Consideration of safety factors of 10 or higher maybe necessary depending on the application such as life safety.

**DESIGN CRITERIA (ALLOWABLE STRESS DESIGN)**

**Combined Loading**

For anchors loaded in both shear and tension, the combination of loads should be proportioned as follows:

$$\left(\frac{N_u}{N_n}\right)^{\frac{5}{3}} + \left(\frac{V_u}{V_n}\right)^{\frac{5}{3}} \leq 1 \quad \text{OR} \quad \left(\frac{N_u}{N_n}\right) + \left(\frac{V_u}{V_n}\right) \leq 1$$

Where: *N<sub>u</sub>* = Applied Service Tension Load  
*N<sub>n</sub>* = Allowable Tension Load  
*V<sub>u</sub>* = Applied Service Shear Load  
*V<sub>n</sub>* = Allowable Shear Load

**Load Adjustment Factors for Spacing and Edge Distances**

Anchor Installed in Normal-Weight Concrete					
Anchor Dimension	Load Type	Critical Distance (Full Anchor Capacity)	Critical Load Factor	Minimum Distance (Reduced Capacity)	Minimum Load Factor
Spacing ( <i>s</i> )	Tension and Shear	<i>s<sub>cr</sub></i> = 3.0 <i>h<sub>v</sub></i>	<i>F<sub>N<sub>S</sub></sub></i> = <i>F<sub>V<sub>S</sub></sub></i> = 1.0	<i>s<sub>min</sub></i> = 1.5 <i>h<sub>v</sub></i>	<i>F<sub>N<sub>S</sub></sub></i> = <i>F<sub>V<sub>S</sub></sub></i> = 0.50
Edge Distance ( <i>c</i> )	Tension	<i>c<sub>cr</sub></i> = 12 <i>d</i>	<i>F<sub>N<sub>C</sub></sub></i> = <i>F<sub>V<sub>C</sub></sub></i> = 1.0	<i>c<sub>min</sub></i> = 6 <i>d</i>	<i>F<sub>N<sub>C</sub></sub></i> = 0.90
	Shear <sup>1</sup>	<i>c<sub>cr</sub></i> = 12 <i>d</i>	<i>F<sub>N<sub>C</sub></sub></i> = <i>F<sub>V<sub>C</sub></sub></i> = 1.0	<i>c<sub>min</sub></i> = 6 <i>d</i>	<i>F<sub>V<sub>C</sub></sub></i> = 0.75

1. Allowable loads for anchors loaded in shear parallel to the edge have no load factor *F<sub>V<sub>C</sub></sub>* = 1.0 when installed at minimum edge distances.

Anchor Installed in Through Steel Deck Structural Lightweight Concrete					
Anchor Dimension	Load Type	Critical Distance (Full Anchor Capacity)	Critical Load Factor	Minimum Distance (Reduced Capacity)	Minimum Load Factor
Spacing ( <i>s</i> )	Tension and Shear	<i>s<sub>cr</sub></i> = 3.0 <i>h<sub>v</sub></i>	<i>F<sub>N<sub>S</sub></sub></i> = <i>F<sub>V<sub>S</sub></sub></i> = 1.0	<i>s<sub>min</sub></i> = 1.5 <i>h<sub>v</sub></i>	<i>F<sub>N<sub>S</sub></sub></i> = <i>F<sub>V<sub>S</sub></sub></i> = 0.50


1. Allowable load values found in the performance data tables are multiplied by reduction factors when anchor spacing or edge distances are less than critical distances. Linear interpolation is allowed for intermediate anchor spacing and edge distances between critical and minimum distances. When an anchor is affected by both reduced spacing and edge distance, the spacing and edge reduction factors must be combined (multiplied). Multiple reduction factors for anchor spacing and edge distance may be required depending on the anchor group configuration.

**DESIGN CRITERIA (ALLOWABLE STRESS DESIGN)**

**Load Adjustment Factors for Normal-weight and Lightweight Concrete**


Spacing, Tension ( $F_{N_s}$ ) & Shear ( $F_{V_s}$ ) (Normal-weight and Lightweight Concrete over deck)			
Dia. (in.)	1/4	3/8	1/2
$h_v$ (in.)	5/8	3/4	1
$s_{cr}$ (in.)	1 7/8	2 1/4	3
$s_{min}$ (in.)	1	1 1/8	1 1/2
Spacing, $s$ (in.)	1	0.50	
	1 1/8	0.60	
	1 1/2	0.80	0.50
	1 7/8	1.00	0.63
	2		0.67
	2 1/4		0.75
	2 1/2		0.83
	3		1.00

Notes: For anchors loaded in tension and shear, the critical spacing ( $s_{cr}$ ) is equal to 3 embedment depths ( $3h_v$ ) at which the anchor achieves 100% of load. Minimum spacing ( $s_{min}$ ) is equal to 1.5 embedment depths ( $1.5h_v$ ) at which the anchor achieves 50% of load.




Edge Distance, Tension ( $F_{N_e}$ ) (Normal-weight concrete only)			
Dia. (in.)	1/4	3/8	1/2
$c_{cr}$ (in.)	3	4 1/2	6
$c_{min}$ (in.)	1 1/2	2 1/4	3
Edge Distance, $c$ (in)	1 1/2	0.90	
	2	0.93	
	2 1/4	0.95	0.90
	2 1/2	0.97	0.91
	3	1.00	0.93
	4		0.98
	4 1/2		1.00
	5		0.97
	6		1.00

Notes: For anchors loaded in tension, the critical edge distance ( $c_{cr}$ ) is equal to 12 anchor diameters ( $12d$ ) at which the anchor achieves 100% of load. Minimum edge distance ( $c_{min}$ ) is equal to 6 anchor diameters ( $6d$ ) at which the anchor achieves 90% of load.



Edge Distance, Shear ( $F_{V_e}$ ) (Normal-weight concrete only)			
Dia. (in.)	1/4	3/8	1/2
$c_{cr}$ (in.)	3	4 1/2	6
$c_{min}$ (in.)	1 1/2	2 1/4	3
Edge Distance, $c$ (in)	1 1/2	0.75	
	2	0.83	
	2 1/4	0.88	0.75
	2 1/2	0.92	0.78
	3	1.00	0.83
	4		0.94
	4 1/2		1.00
	5		0.92
	6		1.00

Notes: For anchors loaded in shear, the critical edge distance ( $c_{cr}$ ) is equal to 12 anchor diameters ( $12d$ ) at which the anchor achieves 100% of load. Minimum edge distance ( $c_{min}$ ) is equal to 6 anchor diameters ( $6d$ ) at which the anchor achieves 75% of load.



**ORDERING INFORMATION**

**Carbon Steel Mini Dropin**

Cat No.	Rod/Anchor Dia.	Drill Diameter	Overall Length	Standard Box	Standard Ctn.
6335	1/4"	3/8"	5/8"	100	1,000
6322	3/8"	1/2"	3/4"	100	1,000
6337	1/2"	5/8"	1"	50	500



**Setting Tool for Mini Dropin**

Cat No.	Mini Dropin Size	Standard Box	Standard Carton
6336	1/4"	1	50
6323	3/8"	1	50
6338	1/2"	1	50



**Accu-Bit™ Drill Stop for Mini Dropin**

Cat No.	Rod/Anchor Size	Standard Box
0398	1/2" Accu-Bit for 3/8" Mini-Dropin	1

